


# SORTING GRAPPLE

TORO LOCO



| Requirements                                                                                                                                                                         | Advantages and Benefits                                                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Strong and easily accessible central structure.</li> <li>Rotating fifth wheel and central hydraulic joint.</li> <li>Jaws in HB400.</li> </ul> | <ul style="list-style-type: none"> <li>Excellent performance in any situation.</li> <li>Strong and Secure grip in any application.</li> </ul> |

IT IS KNOWN AS "THE HAND OF THE CONSTRUCTION SITE".  
PERFECT FOR GRABBING, MOVING, ROTATING, SUPPORTING, AND  
DEMOLISHING NON-REINFORCED STRUCTURES.



Selector grab for mini, midi and excavators from 1.5 up to 30 tons. This extremely versatile grab is widely employed for recycling, handling and demolition of non reinforced structures. It is used on construction sites for brick demolition, waste, wood, paper aluminium and plastic handling, or where it is necessary to select or move material. It is considered a sort of "helping hand" of the construction site. Sturdy construction, high efficiency jaws movement, it features two jaws built in high tensile steel HB400 operated by an hydraulic cylinder and 360° hydraulic rotation. Upper flange easy to match with any kind of coupler, either direct or quick.

|  | Model       | Weight | Opening | <br>Oil | <br>Pressure | <br>Rotation |
|-------------------------------------------------------------------------------------|-------------|--------|---------|--------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Ton                                                                                 | Code        | Kg     | mm      | l/min                                                                                      | BAR                                                                                               | Oil - Pressure                                                                                    |
| 1,0 - 3,0                                                                           | <b>G10</b>  | 70     | 770     | 15                                                                                         | 200                                                                                               | 10/80                                                                                             |
| 3,0 - 6,0                                                                           | <b>G25</b>  | 220    | 1160    | 35                                                                                         | 250                                                                                               | 10/80                                                                                             |
| 5,0 - 10                                                                            | <b>G35</b>  | 330    | 1400    | 50                                                                                         | 250                                                                                               | 20/80                                                                                             |
| 7,0 - 12                                                                            | <b>G45</b>  | 460    | 1500    | 80                                                                                         | 250                                                                                               | 20/80                                                                                             |
| 12 - 20                                                                             | <b>G95</b>  | 960    | 1700    | 100                                                                                        | 300                                                                                               | 50/100                                                                                            |
| 18 - 30                                                                             | <b>G150</b> | 1500   | 1950    | 120                                                                                        | 300                                                                                               | 50/100                                                                                            |